

IN THE CLAIMS

Please amend the claims as follows:

1 (Currently Amended): An interface circuit capable of allowing transmission of data from a detachable card-type memory, which requires access by sectors, to an electronic device, comprising:

a reading unit that reads document image data from at least one of a printer, a copying machine, and a facsimile for a plurality of sectors from the card-type memory;

a buffer in the reading unit that stores the image data read and has a capacity to store data for a plurality of sectors;

a receiver that receives from the electronic device a read-access control command for the image data stored in the buffer;

a data checker that decides whether the image data corresponding to the read-access control command exists among the data stored in the buffer; and

a transmitter that transmits the image data from the buffer to the electronic device when the data checker decides that data corresponding to the read-access control command exists among the data stored in the buffer.

2 (Original): The interface circuit according to claim 1, further comprising a data deleter that deletes data in the buffer, wherein

if the data checker decides that data corresponding to the read-access control command does not exist among the data stored in the buffer, the data deleter deletes from the buffer data that was sent by the transmitter to the electronic device at an oldest period, the reading unit reads from the card-type memory data corresponding to the read-access control command and stores the data read into the buffer, and the transmitter transmits to the

electronic device data corresponding to the read-access control command from among the data stored in the buffer.

3 (Original): The interface circuit according to claim 1, wherein the card-type memory is a secure digital card.

4 (Original): The interface circuit according to claim 1, wherein the buffer has a capacity to store data for at least two sectors.

5 (Currently Amended): An application specific integrated circuit having at least one application function from among an image processing function, an image input/output function, and a data communication function, the application functions sharing at least one of a memory and a hard disk as common resources, comprising:

an interface circuit capable of allowing transmission of data from a detachable card-type memory, which requires access by sectors, to an electronic device, the interface circuit including

a reading unit that reads image data from at least one of a printer, a copying machine, and a facsimile for a plurality of sectors from the card-type memory;

a buffer in the reading unit that stores the image data read and has a capacity to store data for a plurality of sectors;

a receiver that receives from the electronic device a read-access control command for data stored in the buffer;

a data checker that decides whether the image data corresponding to the read-access control command exists among the data stored in the buffer; and

a transmitter that transmits the image data from the buffer to the electronic device

when the data checker decides that data corresponding to the read-access control command exists among the data stored in the buffer.

6 (Original): The application specific integrated circuit according to claim 5, wherein the interface circuit further includes a data deleter that deletes data in the buffer, and

if the data checker decides that data corresponding to the read-access control command does not exist among the data stored in the buffer, the data deleter deletes from the buffer data that was sent by the transmitter to the electronic device at an oldest period, the reading unit reads from the card-type memory data corresponding to the read-access control command and stores the data read into the buffer, and the transmitter transmits to the electronic device data corresponding to the read-access control command from among the data stored in the buffer.

7 (Original): The application specific integrated circuit according to claim 5, wherein the card-type memory is a secure digital card.

8 (Original): The application specific integrated circuit according to claim 5, wherein the buffer has a capacity to store data for at least two sectors.

9 (Currently Amended): An image forming apparatus having at least one application function among an image processing function, an image input/output function, and a data communication function, comprising:

an application specific integrated circuit in which the application functions can share at least one of a memory and a hard disk as common resources, the application specific integrated circuit including an interface circuit capable of allowing transmission of data from

a detachable card-type memory, which requires access by sectors, to an electronic device, the interface circuit including

a reading unit that reads image data from at least one of a printer, a copying machine, and a facsimile for a plurality of sectors from the card-type memory;

a buffer in the reading unit that stores the image data read and has a capacity to store data for a plurality of sectors;

a receiver that receives from the electronic device a read-access control command for data stored in the buffer;

a data checker that decides whether the image data corresponding to the read-access control command exists among the data stored in the buffer; and

a transmitter that transmits the image data from the buffer to the electronic device when the data checker decides that data corresponding to the read-access control command exists among the data stored in the buffer.

10 (Original): The image forming apparatus according to claim 9, wherein the interface circuit further includes a data deleter that deletes data in the buffer, and

if the data checker decides that data corresponding to the read-access control command does not exist among the data stored in the buffer, the data deleter deletes from the buffer data that was sent by the transmitter to the electronic device at an oldest period, the reading unit reads from the card-type memory data corresponding to the read-access control command and stores the data read into the buffer, and the transmitter transmits to the electronic device data corresponding to the read-access control command from among the data stored in the buffer.

11 (Original): The image forming apparatus according to claim 9, wherein the card-

type memory is a secure digital card.

12 (Original): The image forming apparatus according to claim 9, wherein the buffer has a capacity to store data for at least two sectors.

13 (Original): The image forming apparatus according to claim 9, wherein a program stored in the card-type memory is directly executed.